



SEAL 62 Base



SEAL 62 Base

The SEAL 62 Base laminator represents SEAL's offering for the sign and display market. Ideal for mounting and laminating pressure sensitive solutions up to 1.600 mm, this machine represents a flexible package at an affordable price, yet without compromising its functionality.

The SEAL 62 Base is a pressure sensitive machine with heat assist on the top roller to provide superb results with a wide range of materials. Whatever the experience of the operator, the SEAL 62 Base will prove to be a simple machine to use and will deliver genuine flexibility and high performance levels for the small to medium sized end user.

Having great capability delivered at an affordable price, the 62 Base is ideal for signmakers. It will provide the means for these users to finish their images and create more applications thereby generating greater profitability. This laminator is also suitable for small to medium display based businesses who want to provide a wider range of applications and have no need for an encapsulating machine.

The SEAL 62 Base is ideal for producing a wide variety of applications (pressure sensitive materials only).

Ease of use:

- ergonomic control panel for ease of use
- auto grip shafts for user friendly webbing
- swing up feed table to facilitate easy set up
- flip-up roll trough



SEAL 62 Base

Technical Specifications SEAL 62 Base

- 1.600 mm working width to cope with a wide range of media performance
- adjustable pressure and speed settings for maximum versatility
- 50 mm nip opening to cover a wide range of substrates, suitable for working with a sled for road signs
- nip pressure 1N/mm
- heat assisted top roller for superb lamination performance
- upper Roller, maximum Temperature 40°C
- 5 m/min max speed for improved productivity
- manual nip adjustment for precise operation
- robust, free standing design
- foot switch for hands free operation
- self checking safety eyes for increased operator safety
- Dimensions: Width 2.090 mm, Height 1.326 mm, Working Height 900 mm
Depth (excl. table) 483 mm, Depth (incl. in-feed table) 590 mm
- Shipping Dimensions: Width 2.184 mm, Height 1.550 mm, Depth 762 mm
- Net Weight: 240 kg, Shipping Weight: 300 kg
- Warranty: 1 Year, on the base of "Bring-In"
- Electrical Requirements 1N/PE 230VAC +/- 10%, 50/60 Hz, 8,5A
- CE certified

Options:

- roll-to-roll option for volume production
- bottom re-wind option to run products with release liner from the bottom supply shaft

