



SEAL 62 Pro D



SEAL 62 Pro D

The SEAL 62 Pro D is the next generation professional laminator, an evolution of the successful SEAL 62 Plus.

With fully adjustable temperature, speed and pressure settings the SEAL 62 Pro D is ideal for the more experienced user who requires a highly versatile laminator.

The SEAL 62 Pro D is capable of running a wider range of media and can generate higher process speeds, which make this machine ideal for businesses that are looking to build in extra capacity and more versatility. Capable of mounting, laminating and encapsulating prints up to 1600 mm, the machine can be used with the extensive range of Welte Professional laminating films, adhesives and substrates.

The SEAL 62 Pro D features unique design elements such as an ergonomic touch pad control panel for ease of use. The Easy Feed table with built-in tensioning rollers and the flip down image guide guarantee for smooth and optimum infeed of the media. The outfeed slitters can trim the output to size needed.


These features maximize the performance and versatility of the SEAL 62 Pro D without compromising its user friendly nature.



SEAL 62 Pro D

technical features SEAL 62 Pro D

- Adjustable settings for increased capacity and versatility
- 1600 mm working width to cope with a wide range of media
- huge flexibility due to "combi shaft"- technology
- optimal processing of soft substrates by an elaborated roller concept (bompage)
- the maximum speed of 6m/min for increased production capacity
- Rollerheating: top and main roller, maximum roller temperature 140°C
- detachable safety guide
- robust, high-quality
- foldable drawing rollers for waveless encapsulation results and an easy changeover on different manufacturing processes for example handling of rigid material
- an optional feed-in table with braked roller system for an ideal material feeding
- precise manual adjustment of the roller pitch (38 mm) by handwheel
- The contact pressure of max. 2.5 N/mm ensures excellent cold laminating results without silvering effects
- Ventilation system for additional cooling for encapsulation applications
- Dimensions: Width 2.232 mm, Height 1.407 mm, Working Height 890 mm, Depth (excl. table) 666 mm, Depth (incl. in-feed table) 920 mm
- Shipping Dimensions: Width 2.280 mm, Height 1.675 mm, Depth 900 mm
- Net Weight: 490 kg, Shipping Weight: 540 kg
- Warranty: 1 Year, based of "Bring-In"
- Electrical Requirements: 1N/PE 230 VAC +/- 10%, 50/60 Hz, 16A



Ease of use:

- Ergonomic touch pad control panel
- Output slitters to trim the output to size during operation
- High release silicone rollers for easy cleaning
- Drop-in supply shafts with autogrip for easy loading of materials
- New design for swing up feed table to support media handling and set-up
- Simple film tension adjustment
- Automatic upper take-up shaft for removing release liners
- Built-in roll-to-roll
- Manual nip adjustment for precise operation on both front and back of the machine

Options:

- foldable feed-in table with braked roller system, incl. safety guide
- 2 adjustable cutting devices (lengthwise)

Safety:

- Foot switch for hands free operation
- Comprehensive safety system with emergency stops and self-checking safety eyes
- CE certified