



SEAL 62 Pro S



SEAL 62 Pro S

With full independent control over pressure and speed, the SEAL 62 Pro S is ideal for both new and experienced image finishers who require a highly capable laminator but have no need for hot encapsulation. The 62 Pro S is based on the widely acclaimed 62 Pro D and features the same high pressure nip system. This delivers superb results whatever the application required.

The SEAL 62 Pro S is perfect for mounting and laminating up to 1600 mm. The 62 Pro S includes a heated top roller, fully adjustable up to 140°C, for enhanced lamination. The machine is ideal for medium to large volume production environments where control and productivity are key requirements. The SEAL 62 Pro S has four material stations. The two bottom stations have combi-shafts (unwind or rewind). This provides maximum flexibility, enables roll-to-roll operation, and allows for the use of a wider range of consumables.

The two rear stations are of a swing-out design which facilitates easy loading and reduces the space required to site the machine. The 62 Pro S features a feed table with built-in trough, for the easier handling of large-size media. The table swings up allowing full and easy access to the rollers when webbing the machine. An additional hand wheel at the back gives optimum output control and simplifies the webbing process even further. Roll-to-roll workflow is a given.



SEAL 62 Pro S

Technical Specifications SEAL 62 Pro S

- fully adjustable pressure and speed settings for maximum versatility
- 2,5 N/mm line pressure for superior cold lamination
- 38 mm nip opening to cover a wide range of substrates
- 1600 mm working width to cope with a wide range of media
- 2 combi-shafts (bottom) for roll-to-roll operation
- variable roller technology for better processing of soft substrates
- maximum speed of 6 m/min for increased production capacity
- upper Roller, maximum Temperature 62 S 140°C
- manual nip adjustment (front & back) for precise operation
- robust, free standing design
- foot switch for hands free operation
- removable safety guide
- self checking safety eyes for increased operator safety
- Dimensions: Width 2.232 mm, Height 1.407 mm, Working Height 890 mm, Depth (excl. table) 666 mm, Depth (incl. in-feed table) 920 mm
- Shipping Dimensions: Width 2.280 mm, Height 1.675 mm, Depth 900 mm
- Net Weight: 490 kg, Shipping Weight: 540 kg
- Warranty: 1 Year, on the base of "Bring-In"
- Electrical Requirements: 1N/PE 230 VAC +/- 10%, 50/60 Hz, 16A
- CE certified

Ease of use:

- ergonomic control panel for ease of use
- swing out supply shafts for easy loading
- auto grip supply shafts for user friendly material loading
- flip-up roll trough
- roll-to-roll built-in
- auto grip re-wind shafts for more effective take up of release liners
- outboard brakes for greater control of material unwind
- additional hand wheel at the back
- auto grip shaft storage facility

