

## Welte 62 Base



### Welte 62 Base

The universal laminator for quick, easy mounting and laminating work, as well as the application of double-sided adhesive film and application tape.

The system's advantages are particularly evident in its clear concept aimed at user-friendliness and in the quality of the rollers with a special, not too hard rubber mixture. The maximum passage height is 40 mm. The maximum processing speed is stepless adjustable up to 5 meters per minute.

The rollers have a diameter of 116 mm and are equipped with a non-stick coating. The upper roller is raised and lowered pneumatically, the pressure is variably set with a pressure regulator, the pressure is displayed with a pressure gauge.

The 3 material shafts (optionally 4) ensure easy handling and quick changing of the material. The upper roller can be pre-programmed to be heated to 30/40/50°C.

#### Key benefits:

- Clear, manageable machine concept allows for easy handling
- Quick and easy changing of material
- Versatile system for all standard applications in advertising technology



## Welte 62 Base

### Technical Specifications Welte 62 Base

- Clear, easy-to-understand machine design
- 3 material shafts "easy-to-use" - optionally with 4 shafts
- suitable for all common applications in advertising market
- Speed control via rotary control
- Pneumatic raising and lowering of the upper roller via electric buttons
- Roller pressure is set with a pressure regulator and displayed via pressure gauge
- Additional foot pedal to lower the top roller when setting up the machine
- maximum working width 1600 mm
- maximum opening between the rollers 40 mm
- upper pressure roller can be heated (30° - 40° - 50°C pre-programmed)
- high-quality rollers with a diameter of 116 mm
- electronically controlled material feed, stepless variable from 0 to 5 m/min.
- Feed command possible via control panel or foot pedal
- infeed table that can be swiveled upwards, made of aluminum, for easy access to the rollers
- Photoelectric light barrier and Emergency Stop button for maximum safety
- Dimensions (W x D x H) 2,000 mm x 675 mm x 1,500 mm
- Weight: 215 kg
- Warranty: 1 year - "Bring-In" basis
- Power supply: 230V 50/60Hz 2500W
- Compressed air supply: 6 bar / 5 liters/minute  
\* a compressor is not included in delivery \*
- Safety system
- CE-certified

### Options:

- Unwind tray for loosely rolled material to be laminated
- Feed-in guide for perfect material guidance
- Rear cutting unit with 2 cutting blades
- Additional winding shaft at the rear for R2R processing

